

MODELLO	MODELL		20 HP
MODEL	MODÈLE		74841480
COMPRESSORE	KOMPRESSOR		BITZER
COMPRESSOR	COMPRESSEUR		4GE-23Y
POTENZA FRIGORIFERA	KALTELEISTUNG	W	49350 (-10/+40)
REFRIGERATION POWER	UISSANCE FRIGORIFIQUE		20200 (-30/+40)
POTENZA ASSORBITA	LEISTUNGS-AUFNAHME	W	12090 (-30/+40)
ABSORBED POWER	PUISSANCE ASSORBEE		
MASSIMA CORRENTE	MAX STROM-AUFNAHME	A	62
MAX CURRENT	COURANT MAXIMUM		
TENSIONE E FREQUENZA	NETZSPANNUNG UND FREQUENZ	V / Hz	400 / 3+N+T / 50
VOLTAGE & FREQUENCY	TENSION ET FREQUENCE		
PESO NETTO	REINGEWICHT	KG	510
NET WEIGHT	POIDS NET		
RUMORE	LAUTSTARKE	DB	122
NOISE	BRUIT	5M	
DIMENSIONI	AMBENSUGGEN	MM	2180 x 1170 x 1208
DIMENSIONS	DIMENSIONS	LxPxH	
CLASSE CLIMATICA	KLIMATISCHE KLASSE	INDEX	5 (40°C)
CLIMATIC CLASS	CLASSE CLIMATIQUE		> -15°C
CAVI ELETTRICI	ELEKTROKABEL	P x MMQ	4 x 10
ELECTRICAL CABLE	CÂBLES ÉLECTRIQUES		14 x 1.5
DIMENSIONI IMBALLO	AMBENSUGGEN VERPACKUNG	MM	2340 x 1330 x 1430
PACKING DIMENSIONS	DIMENSIONS EMBALLAGE	LxPxH	
VENTILATORE	VENTILATOR	MM	Ø 630 (900 rpm)
FAN	VENTILATEUR	MC/H	19000
Ø TUBI GAS	Ø LEITUNGEN GAS	10 M	28 - 28 - 54 mm
Ø GAS PIPES	Ø TUYAUX GAZ	20 M	28 - 28 - 54 mm
		30 M	28 - 28 - 54 mm
		40 M	28 - 28 - 54 mm
		50 M	28 - 28 - 54 mm
CARICA GAS INIZIALE *	ANFÄNGLICHE GAS BELADT *	10 M	15 Kg
START GAS CHARGE *	CHARGE DE GAZ INITIALE *	20 M	16 Kg
		30 M	17 Kg
		40 M	18 Kg
		50 M	19 Kg

* Dopo aver eseguito la carica gas iniziale, aggiungere gas fino al riempimento della spia di liquido.

* After the initial gas charge, add gas to the filling of the sight glass.

* Nach der Durchführung der anfänglichen Gasladung, fügen Gas zum Füllen des Schauglases.

* Après avoir effectué la charge de gaz initial, ajouter du gaz de remplissage du verre de visée.

