



MODELLO	MODELL		4 HP - SILENT
MODEL	MODÈLE		74841680
COMPRESSORE	KOMPRESSOR		BITZER
COMPRESSOR	COMPRESSEUR		4EES-4Y
POTENZA FRIGORIFERA	KALTELEISTUNG	W	12740 (-10/+40)
REFRIGERATION POWER	UISSANCE FRIGORIFIQUE		5060 (-30/+40)
POTENZA ASSORBITA	LEISTUNGS-AUFNAHME	W	3250 (-30/+40)
ABSORBED POWER	PUISSANCE ASSORBEE		
MASSIMA CORRENTE	MAX STROM-AUFNAHME	A	21
MAX CURRENT	COURANT MAXIMUM		
TENSIONE E FREQUENZA	NETZSPANNUNG UND FREQUENZ	V / Hz	400 / 3+N+T / 50
VOLTAGE & FREQUENCY	TENSION ET FREQUENCE		
PESO NETTO	REINGEWICHT	KG	240
NET WEIGHT	POIDS NET		
RUMORE	LAUTSTARKE	DB	45
NOISE	BRUIT	5M	
DIMENSIONI	AMBENSUGGEN	MM	1352 x 760 x 892
DIMENSIONS	DIMENSIONS	LxPxH	
CLASSE CLIMATICA	KLIMATISCHE KLASSE	INDEX	5 (40°C)
CLIMATIC CLASS	CLASSE CLIMATIQUE		> -15°C
CAVI ELETTRICI	ELEKTROKABEL	P x MMQ	4 x 2.5
ELECTRICAL CABLE	CÂBLES ÉLECTRIQUES		12 x 1
DIMENSIONI IMBALLO	AMBENSUGGEN VERPACKUNG	MM	1520 x 825 x 1064
PACKING DIMENSIONS	DIMENSIONS EMBALLAGE	LxPxH	
VENTILATORE	VENTILATOR	MM	ø 450 (900 rpm)
FAN	VENTILATEUR	MC/H	3827
ø TUBI GAS	ø LEITUNGEN GAS	10 M	12 - 12 - 22 mm
ø GAS PIPES	ø TUYAUX GAZ	20 M	12 - 12 - 28 mm
		30 M	12 - 12 - 28 mm
		40 M	12 - 12 - 28 mm
		50 M	12 - 12 - 35 mm
CARICA GAS INIZIALE *	ANFÄNGLICHE GAS BELADT *	10 M	3.5 Kg
START GAS CHARGE *	CHARGE DE GAZ INITIALE *	20 M	4 Kg
		30 M	4.5 Kg
		40 M	5 Kg
		50 M	5.5 Kg



* Dopo aver eseguito la carica gas iniziale, aggiungere gas fino al riempimento della spia di liquido.

* After the initial gas charge, add gas to the filling of the sight glass.

* Nach der Durchführung der anfänglichen Gasladung, fügen Gas zum Füllen des Schauglases.

* Après avoir effectué la charge de gaz initial, ajouter du gaz de remplissage du verre de visée.