



RIF. UCR

MODELLO	MODELL		40 HP
MODEL	MODÈLE		74841488
COMPRESSORE	KOMPRESSOR		BITZER
COMPRESSOR	COMPRESSEUR		6FE-44Y
POTENZA FRIGORIFERA	KALTELEISTUNG	W	87500 (-10/+40)
REFRIGERATION POWER	UISSANCE FRIGORIFIQUE		36250 (-30/+40)
POTENZA ASSORBITA	LEISTUNGS-AUFNAHME	W	22400 (-30/+40)
ABSORBED POWER	PUISSANCE ASSORBEE		
MASSIMA CORRENTE	MAX STROM-AUFNAHME	A	110
MAX CURRENT	COURANT MAXIMUM		
TENSIONE E FREQUENZA	NETZSPANNUNG UND FREQUENZ	V / Hz	400 / 3+N+T / 50
VOLTAGE & FREQUENCY	TENSION ET FREQUENCE		PART WINDING
PESO NETTO	REINGEWICHT	KG	2150
NET WEIGHT	POIDS NET		
RUMORE	LAUTSTARKE	DB	128
NOISE	BRUIT	5M	
DIMENSIONI	AMBENSUGGEN	MM	2800 x 1300 x 2212
DIMENSIONS	DIMENSIONS	LxPxH	
CLASSE CLIMATICA	KLIMATISCHE KLASSE	INDEX	5 (40°C)
CLIMATIC CLASS	CLASSE CLIMATIQUE		> -15°C
CAVI ELETTRICI	ELEKTROKABEL	P x MMQ	4 x 16 (x2)
ELECTRICAL CABLE	CÂBLES ÉLECTRIQUES		14 x 1.5
DIMENSIONI IMBALLO	AMBENSUGGEN VERPACKUNG	MM	2900 x 1400 x 2312
PACKING DIMENSIONS	DIMENSIONS EMBALLAGE	LxPxH	
VENTILATORE	VENTILATOR	MM	ø 800 (900 rpm)
FAN	VENTILATEUR	MC/H	41885
ø TUBI GAS	ø LEITUNGEN GAS	10 M	28 - 28 - 54 mm
ø GAS PIPES	ø TUYAUX GAZ	20 M	28 - 28 - 54 mm
		30 M	28 - 28 - 54 mm
		40 M	28 - 28 - 54 mm
		50 M	28 - 28 - 54 mm
CARICA GAS INIZIALE *	ANFÄNGLICHE GAS BELADT *	10 M	30 Kg
START GAS CHARGE *	CHARGE DE GAZ INITIALE *	20 M	31 Kg
		30 M	32 Kg
		40 M	33 Kg
		50 M	34 Kg

* Dopo aver eseguito la carica gas iniziale, aggiungere gas fino al riempimento della spia di liquido.

* After the initial gas charge, add gas to the filling of the sight glass.

* Nach der Durchführung der anfänglichen Gasladung, fügen Gas zum Füllen des Schauglases.

* Après avoir effectué la charge de gaz initial, ajouter du gaz de remplissage du verre de visée.

